**Amendments to the Claims:**

1. (currently amended)    An electronic apparatus comprising:

5    a controller having a serial AT Attachment (SATA) port, and being electrically coupled to a host through the SATA port; and

a plurality of peripheral devices electrically coupled to the controller using digital means;

10    wherein the controller is for allowing allows the host to access the peripheral devices through the SATA port; and

the peripheral devices include a first peripheral device and a second peripheral device, and the controller is further for directly transferring data stored on the first

15    peripheral device to the second peripheral device according to a command from the host but without buffering the data in the host and without transferring the data through the SATA port.

2. (original)    The electronic apparatus of claim 1, wherein the controller operates as a

20    port multiplier to allow the host to access the peripheral devices through the SATA port.

3. (currently amended)    The electronic apparatus of claim 1, wherein the peripheral devices electrically coupled to the controller simultaneously at least comprise an

25    optical storage device and a non-volatile storage device.

4. (original)    The electronic apparatus of claim 3, wherein the non-volatile storage device is a flash card access device or a hard-disk drive.

5. (cancelled)

6. (currently amended)   A method of accessing an electronic apparatus, the method

5      comprising:

       providing a controller having a serial AT Attachment (SATA) port, and being

       electrically coupled to a host through the SATA port;

10     electrically coupling a plurality of peripheral devices to the controller using digital

       means, wherein the peripheral devices include a first peripheral device and a second

       peripheral device; and

       accessing the peripheral devices from the host through the SATA port; and

15

       directly transferring data stored on the first peripheral device to the second

       peripheral device according to a command from the host but without buffering the

       data in the host and without transferring the data through the SATA port.

20     7. (original)   The method of claim 6, furthering comprising operating the controller as a

       port multiplier to allow the host to access the peripheral devices through the SATA

       port.

       8. (currently amended)   The method of claim 6, wherein the peripheral devices

25     electrically coupled to the controller simultaneously at least comprise an optical

       storage device and a non-volatile storage device.

       9. (currently amended)   The method of claim 8 claim 6, wherein the non-volatile storage

3

device is a flash card access device or a hard-disk drive.

10. (cancelled)

5